

BEECH VIBORG

Beech Viborg is a floor in which we have mixed the lighter surface wood and reddish core of beech.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|--|----------------------|------------------------|---------------------|----------------------------|-------------|-------------|
| Article Number | 153N18BK50KW0 | Wood Species | Beech | Moisture content | EN13183 | 7%±2% |
| Surface Treatment | Satin lacquer | Design | 3-strip | Minimun Mean Density kg/m³ | | >500 kg/m³ |
| Dimensions | 2423 x 200 x 15 mm | Grading | Variation (Town) | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Weight per Package | 23 kg | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| Area per Package | 2.91 m ² | Collection | Nordic Naturals | Content PCP | CEN/TR14823 | ≤5 x 10-6n |
| Area Per Board | 0.485 m ² | | Collection | Breaking Strength N/mm² | EN1533 | NPD |
| | | Natural/Stained | Natural | Thermal Conductivity | EN12664 | 0,14 W/mK |
| DETAIL DESCRIPTION | | Brinell Value | 3, 8 | Thermal Resistance R-Value | | .11 (m2K/W) |
| Even light colour with minor variations. Small sized knots in limited numbers allowed. | | Joint | Woodloo® 5S | Biological Durability | EN350-2 | Class 1 |
| | | Hoor heating | No | CARB2 | | Compliant |
| COLOUR CHANGE | | Wear-layer material | Hardwood | CARDZ | | Compliant |
| Changes from pink/tan tones to amber. | | Core material | Pine/Spruce lamella | | | |
| | | Thickness | 15 mm | | | |
| | | Installation | Floating, glue-down | | | |

7393969020121

method **EAN Code**

CERTIFICATE

